## MC210




## Robust, reliable ID card printing for all environments



Matica's MC210 is a **robust** and **reliable** option for ID card issuance, its ruggedized, stylish design makes it suitable for use in any environment.

**Upgradable** from single to dual-sided, the MC210 is also available with multiple secure card **encoding options** and can be integrated seamlessly with an **inline laminator**.

The MC210 is perfect for schools, colleges and medium sized businesses for mid-volume issuance. Based on Matica's established print engine, when it comes to secure and reliable ID card printing, you can trust the MC210 to deliver.



## MC210 delivers...

MC2IO

- Robust, reliable build quality
- High quality 300dpi printing
- Up to 180 color cards per hour
- Versatility including multiple encoding and lamination
- ▶ 3 years warranty



Ideal for...

Mid volume card issuance



# **MC210**

## Printer specifications

#### Print technology

Dye-sublimation, direct-to-card Rewritable

#### Print resolution

300 dpi

#### Print area

53.98 x 85.6mm / 3.370" x 2.125" (CR-80 cards)

#### Print speed

• 180 cph (YMCKO single-side) • 1000 cph (monochrome printing)

#### Print mode

Single or dual-sided (optional)

Printer memory

128 Mb

**Communications interface** 

USB 2.0, Ethernet 10BaseT, 100BaseT

#### Easy to use, plug and print operation

LCD display with graphical notifications

- 4 x LED status indicators
- Full front operation
- Drop in ribbon cassette with easy handling · Automatic ribbon identification and setting
- · Easy reach power button
- · Easy maintenance access

#### Printer security

Support for Kensington® security lock

#### Printer dimensions (HxWxD)

256 x 202 x 405 mm / 10.6" x 7.9" x 15.9"

#### Weight

6.8 kg, 15 lb

#### Power supply

· 220-240V/110-115V, 50-60 Hz Standby mode and reduced power consumption

#### **Operating environment**

- Temperature: 15°C 40°C. 59°F 104°F • Humidity: 20% - 65% (non-condensing)
- Storage conditions
- Temperature: -5°C to 70°C, 23°F to 158°F
- Humidity: 20% to 70% (non-condensing)

#### Sound (ISO 7779)

Sound pressure less than 48dB (A)

#### Certifications

RoHs, CE, FCC, CQC, UL, WEEE, Proposition 65 (California, USA)

#### Warranty

3 years (subject to the use of chromXpert® ribbons)



## Global offices

Europe: Switzerland HQ, Italy Asia: Malaysia, India USA: South Carolina HQ, Minneapolis Middle East: Dubai

## Card specifications

#### Input hopper capacity

100 cards (0.76 mm / 30 mil thickness)

#### Output hopper capacity 30 cards (front)

80 cards (rear/reject) Card thickness

• 0.25 mm - 1.25 mm / 10 mil - 50 mil Gauge adjustment

#### Card types

CR-80 PVC, PVC-C

### Software specifications

#### XPS printer driver

Windows<sup>®</sup> (32/64bit) 7, 8.1, 10, 11, Server 2012, 2016, 2019, 2022

#### MacOS

MacOS: from Mavericks 10.9 to Ventura 13.1

### Options

Magnetic stripe encoding

ISO 7811 HiCo/LoCo (factory fit only)

### Smart card / Contactless encoding

Contact PC/SC, EMV compliant

- Smart contact station: ISO 7816-2 ISO14443A, B, ISO15693, MIFARE®, DESFire®,
- HID iClass

#### **Dual-side activation kit**

#### Inline lamination

Single or dual-side, sold with compatiblilty plinth


PR10300016





## Consumables chrom pert

- To ensure print quality and card durability, printhead lifespan and overall printer reliability, use chromXpert ribbons only.
- · Supply cores and cassettes are recyclable. Packaging is recycled.



ChromXpert™ ribbon program		Part No.
YMCKO (250 prints)		PR20307301 PR20319301
YMCKO-K (200 prints)		PR20307302 PR20319302
• ymc-K0 (400 prints, half panel)		PR20319303
• KO (600 prints)		PR20305304
Monochrome K (up to 2	000 prints)	PR20314305
Mono: Silver (up to 500 prints) Mono: Gold (up to 500 prints)		PR20314306 PR20314307
Monochrome: White, Re Blue, Scratch-off (up to 1		Also availabl
Cleaning kit		PR20309610

Authorized reseller / System integrator

maticagroup.com





MC210 Datasheet A4 UK V10

are the property of their respective owners

Data subject to change without notice. All trademarks stated