MC310







Best-in-class secure ID card issuance

STUDENT





Columbus University

NAME: John Harvey DATE OF BIRTH: 01/02/2005 VALID UNTIL: 01/01/30





01/01/30

(01)75842361594750

Matica's MC310 is unrivalled in its **versatility**. It can be upgraded from single to dual-sided and is available with multiple secure card encoding options.

The MC310 integrates seamlessly with both lamination and laser options making it ideal for **secure** ID projects and high volume issuance.

Its excellent build quality is backed by an **industry-leading** four year warranty.



































■ MC310 delivers...

 Versatility - including multiple encoding, lamination and laser options



- ► High quality TruEdge 300dpi printing
- ▶ Up to 180 color cards per hour

■ Ideal for...

- ► Secure ID projects
- ▶ Mid to high volume card issuance

MC310

Printer specifications

Print technology

- · Dye-sublimation, direct-to-card
- Rewritable

Print resolution

• 300 dpi

• 53.98 x 85.6mm / 3.370" x 2.125" (CR-80 cards)

Print speed

- 180 cph (YMCKO single-side)
- 1000 cph (monochrome printing)

Print mode

· Single or dual-sided (optional)

Printer memory

• 128 Mb

Communications interface

• USB 2.0, Ethernet 10BaseT, 100BaseT

Easy to use, plug and print operation

- LCD display with graphical notifications
- · 4 x LED status indicators
- Full front operation
- · Drop in ribbon cassette with easy handling
- · Automatic ribbon identification and setting
- · Easy reach power button
- · Easy maintenance access

Printer security

Support for Kensington® security lock

Printer dimensions (HxWxD)

• 256 x 202 x 405 mm / 10.6" x 7.9" x 15.9"

Weight

• 6.8 kg, 15 lb

Power supply

- · 220-240V / 110-115V, 50-60 Hz
- · Standby mode and reduced power consumption

Operating environment

- Temperature: 15°C to 40°C. 59°F to 104°F
- Humidity: 20% to 65% (non-condensing)

Storage conditions

- Temperature: 5°C to 70°C, 23°F to 158°F
- Humidity: 20% to 70% (non-condensing)

Sound (ISO 7779)

· Sound pressure less than 48dB (A)

RoHs, CE, FCC, CQC, UL, WEEE, Proposition 65 (California, USA), Radio Equipment Directive (RED) (2014/53/EU)

Warranty

4 years (subject to the use of chromXpert® ribbons)

Card specifications

Input hopper capacity

- 100 cards (0.76 mm / 30 mil thickness)
- Single card exception feeding

Output hopper capacity

- 30 cards (front)
- · 80 cards (rear/reject)

Card thickness

- 0.25 mm 1.25 mm / 10 mil 50 mil
- · Gauge adjustment

• CR-80 PVC, PVC-C, rewritable cards

■ Software specifications

XPS printer driver / MacOS

- Windows® (32/64bit) 7, 8.1, 10, 11, Server 2012, 2016, 2019, 2022.
- MacOS Mavericks 10.9 to Ventura 13.1

Integration tools

- FDIsecure® middleware
- · SDK available for system integrators

Options

Magnetic stripe encoding

• ISO 7811 HiCo/LoCo (factory fit only)

Smart card / Contactless encoding

- · Contact PC/SC, EMV compliant
- Smart contact station: ISO 7816-2
- ISO14443A, B, ISO15693, MIFARE®, DESFire®,

Inline lamination

· Single or dual-side, sold with compatiblilty plinth




Printer security

- Mechanical locks
- · Electromagnetic locks

Dual-side activation kit

Consumables chrom pert

- To ensure print quality and card durability, printhead lifespan and overall printer reliability, use chromXpert ribbons only
- · Supply cores and cassettes are recyclable. Packaging is recycled.



ChromXpert™ ribbon program

Part No.

PR20319303

PR20305304

Platinum: PR20307301 · YMCKO (250 prints) Diamond: PR20305301

· YMCKO-K (200 prints) Platinum: PR20307302

Diamond: PR20319302

· ymc-KO (400 prints, half panel)

· GOKO (250 prints) Platinum: PR20305391

Platinum: PR20305392 • SOKO (250 prints)

• UcYMCK (250 prints)
For use with PC/PET cards only PR20307382

· Monochrome K (up to 2000 prints) PR20314305

PR20305304 • Monochrome KO (600 prints)

• Mono: Gold (up to 500 prints) PR20314307

· Monochrome: White, Red, Green, Blue, Scratch-off (up to 1000 prints) Also available

• Mono: Silver (up to 500 prints)

PR20314306

Cleaning kit

PR10300016

· KO (600 prints)

PR20309601



Global offices

Europe: Switzerland HQ, Italy

Asia: Malaysia

USA: South Carolina HQ, Minneapolis

Middle East: Dubai



Authorized reseller / System integrator

Data subject to change without notice. All trademarks stated are the property of their respective owners.

MC310 Datasheet A4 UK V15

