

MC310



Best-in-class secure ID card issuance


















Matica's MC310 is unrivalled in its **versatility**. It can be upgraded from single to dual-sided and is available with multiple secure card encoding options.

Its extensive chromXpert™ consumable program includes secure UV and Sc (pearlescent) ribbon options.

The MC310 integrates seamlessly with both lamination and laser options making it ideal for **secure** ID projects and high volume issuance.

Its excellent build quality is backed by an **industry-leading** four year warranty.

<div>Print type</div> <div></div> <div>Dye sublimation</div>	<div>300 dpi</div> <div></div> <div>Resolution</div>	<div>Print mode</div> <div></div> <div>1 or 2 sided</div>	<div>180 cph</div> <div></div> <div>Full color</div>	<div>1000 cph</div> <div></div> <div>Monochrome</div>
<div>Easy to use</div> <div></div> <div>Plug & print</div>	<div>Input capacity</div> <div></div> <div>x100</div>	<div>Output capacity</div> <div></div> <div>30 front / 80 back</div>	<div>Ethernet</div> <div></div>	<div>LCD display</div> <div></div>
<div>Reject bin</div> <div></div>	<div>Rewritable</div> <div></div>	<div>Cards left</div> <div></div> <div>Indicator</div>	<div>Single wire</div> <div></div> <div>Encoding option</div>	<div>Encoding</div> <div></div> <div>Options</div>



MC310 delivers...

- Versatility - including multiple encoding, lamination and laser options



- Extensive consumables program, including secure ribbons
- High quality TruEdge 300dpi printing
- Up to 180 color cards per hour

Ideal for...

- Secure ID projects
- Mid to high volume card issuance

MC310

Printer specifications

Print technology

- Dye-sublimation, direct-to-card
- Rewritable

Print resolution

- 300 dpi

Print area

53.98 x 85.6mm / 3.370" x 2.125" (CR-80 cards)

Print speed

- 180 cph (YMCKO single-side)
- 1000 cph (monochrome printing)

Print mode

- Single or dual-sided (optional)

Printer memory

128 Mb

Communications interface

USB 2.0, Ethernet 10BaseT, 100BaseT

Easy to use, plug and print operation

- LCD display with graphical notifications
- 4 x LED status indicators
- Full front operation
- Drop in ribbon cassette with easy handling
- Automatic ribbon identification and setting
- Easy reach power button
- Easy maintenance access

Printer security

Support for Kensington® security lock

Printer dimensions (HxWxD)

256 x 202 x 405 mm / 10.6" x 7.9" x 15.9"

Weight

6.8 kg, 15 lb

Power supply

- 220-240V/110-115V, 50-60 Hz
- Standby mode and reduced power consumption

Operating environment

- Temperature: 15°C - 40°C, 59°F - 104°F
- Humidity: 20% - 65% (non-condensing)

Storage conditions

- Temperature: -5°C to -70°C, 23°F to 158°F
- Humidity: 20% to 70% (non-condensing)

Sound (ISO 7779)

Sound pressure less than 48dB (A)

Certifications

RoHs, CE, FCC, CQC, UL, WEEE, Proposition 65 (California, USA)

Warranty

4 years (subject to the use of chromXpert® ribbons)

Card specifications

Input hopper capacity

- 100 cards (0.76 mm / 30 mil thickness)
- LED card level indicator
- Single card exception feeding

Output hopper capacity

- 30 cards (front)
- 80 cards (rear/reject)

Card thickness

- 0.25 mm - 1.25 mm / 10 mil - 50 mil
- Gauge adjustment

Card types

CR-80 PVC, PVC-C, rewritable cards

Software specifications

XPS printer driver / MacOS

- Windows® (32/64bit) 7, 8.1, 10, 11, Server 2012, 2016, 2019, 2022.
- MacOS Mavericks 10.9 to Ventura 13.1

Integration tools

- EDIsecure® middleware
- SDK available for system integrators

Options

Magnetic stripe encoding

ISO 7811 HiCo/LoCo (factory fit only)

Smart card / Contactless encoding

- Contact PC/SC, EMV compliant
- Smart contact station: ISO 7816-2
- ISO14443A, B, ISO15693, MIFARE®, DESFire®, HID iClass®

Inline lamination

Single or dual-side, sold with compatibility plinth



Printer security

- Mechanical locks
- Electromagnetic locks

Communications interface

- WiFi 802.11 a/b/g
- Single wire encoding


Dual-side activation kit

PR10300016



Consumables chromXpert

- To ensure print quality and card durability, printhead lifespan and overall printer reliability, use chromXpert ribbons only.
- Supply cores and cassettes are recyclable. Packaging is recycled.



ChromXpert™ ribbon program	Part No.
• YMCKO (250 prints)	Platinum: PR20307301 Diamond: PR20319301
• YMCKO-K (200 prints)	Platinum: PR20307302 Diamond: PR20319302
• ymc-KO (400 prints, half panel)	PR20319303
• KO (600 prints)	PR20305304
• YMCKScKO (200 prints)	PR20319383
• GOKO (250 prints)	Platinum: PR20305391
• SOKO (250 prints)	Platinum: PR20305392
• UcYMCK (250 prints) For use with PC/PET cards only	PR20307382
• Monochrome K (up to 2000 prints)	PR20314305
• Monochrome KO (600 prints)	PR20305304
• Mono: Silver (up to 500 prints)	PR20314306
• Mono: Gold (up to 500 prints)	PR20314307
• Monochrome: White, Red, Green, Blue, Scratch-off (up to 1000 prints)	Also available
Cleaning kit	PR20309601



Global offices

Europe: Switzerland HQ, Italy, UK and Germany

Asia: Malaysia, China and India

USA: Minneapolis HQ, South Carolina and San Francisco

Middle East: Dubai



Authorized reseller / System integrator

Data subject to change without notice.
All trademarks stated are the property of their respective owners.

MC310 Datasheet A4 UK V8