
S3200





High quality flat card issuance at branch level

Using the same engine as the XID8300 retransfer card printer, the S3200 has been equipped with modified components to make it Mastercard and Visa compliant for the onsite issuance of flat EMV cards for banks, credit unions and other financial institutions wanting to offer their customers personalized payment cards.

The optional IPSC (IP Secure Controller) offers a highperformance operation over Ethernet, featuring secure chip encoding over local area network (LAN) and wide area network (WAN) with data encryption and data compression for network traffic optimization. The S3200 has been equipped with internal electronic locks and mechanical keyed locks on the front door to prevent unauthorized access to the card cartridges and internal reject tray, ensuring that any card issued is secure.



Retransfer

Printing

Distributed


S3200 delivers...


- 300 x 300dpi printing resolution
- Automatic and exception feeder, concealed hopper, reject tray
- Mag ISO and contact/contactless chip encoding
- Single wire connectivity
- Easy set-up
- Robust design with a superior print quality and reliability

Ideal for...

- Low to mid volume financial card programs
- Instant issuance
- Flat bank card personalization

Standard features





45 cph

»))

Standard



Security

80 cph









6

1 Encoding option













Printer specifications

Print technology

• Dye-sublimation retransfer (YMCK)

Thermal transfer (monochrome K)

Print resolution

• 300 dpi

Print area

• ISO CR-80, 85.60 x 53.98 mm

Print speed

- YMC/K+PO printing, Mag ISO encoding: up to
- 45cph • K (front side) printing, Mag ISO encoding: up to 80cph
- Chip encoding: add 6 to 15 seconds (customer application dependent)

Print mode

- Standard: Single-sided
- Optional: Dual-sided

Communications interface

• USB 2.0, Ethernet

Printer security

· Support for Kensington security lock

Dimensions (HxWxD)

• 343 x 411 x 337 mm / 13.5" x 16.2" x 12.8"

Weight

• 15 kg / 33 lb (excluding optional built-in items)

Power supply

• 220-240V/100-120V, 50-60 Hz • FCC, CE, UL, GOST-R, and CCC approved

Operating environment

• Temperature: 15°C - 30°C, 59°F - 86°F • Humidity: 35% - 70% (non-condensing)

Storage conditions

- Temperature: 5°C to 70°C, 23°F to 158°F
- Humidity: 20% to 70% (non-condensing)

Certifications

• RoHs, CE, FCC, CQC, UL, WEEE, Proposition 65 (California, USA)

Warranty

- + 3 year (subject to the use of chromXpert $^{\scriptscriptstyle (\! 8\!)}$ ribbons)
- Printhead: Lifetime warranty (Limited to 100,000 passes)

Card specifications

Input hopper capacity

• 200 cards (0.76 mm / 30 mil thickness)

Output hopper capacity

• 75 cards

10 cards

Reject hopper capacity

Card thickness

• 0.25 mm – 1.02 mm / 10 mil – 40 mil (Hopper adjustment required)

Card types

• ISO CR80, PVC, Composite PVC, PET-G, PC

Software specifications

XPS printer driver

• Windows[®] (32/64bit) 7, 8.1, 10, 11, Server 2012, 2016, 2019, 2022.

Encoding

Magnetic stripe

ISO 7811 HiCo/LoCo (factory fit only)

Smart card / Contactless encoding

- Contact PC/SC, EMV compliant
- Smart contact station: ISO 7816-2
- \bullet ISO14443A, B, ISO15693, MIFARE®, DESFire®, HID iClass®

Options

Printing

Dual-sided printing

Bend remedy

· Bend remedy for card flatness



Consumables chrom Xpert

- To ensure print quality and card durability, printhead lifespan and overall printer reliability, use chromXpert ribbons only.
- Supply cores and cassettes are recyclable. Packaging is recycled.

ChromXpert™ ribbon pro	gram Part No.
YMCK (1000 prints)	Diamond: PR000816
YMCKK (750 prints)	Diamond: PR000817
• K (2200 prints)	Diamond: PR000815
• YMCKPo (750 prints)	Diamond: PR000818
• RT film (1000 prints)	Diamond: PR000819
YMCKUv (750 prints)	Diamond: PR000813
Cleaning Kit	DIC10044

Authorized reseller / System integrator



Global offices

Europe: Switzerland HQ, Italy Asia: Malaysia, India USA: South Carolina HQ, Minneapolis Middle East: Dubai

Data subject to change without notice. All trademarks stated are the property of their respective owners.

S3200 Datasheet A4 UK V1

