





# All-in-one solution for printing, embossing and encoding EMV financial cards




The **S3610** is the result of decades of experience in developing a complete financial card personalization solution. It is a comprehensive instant issuance solution that **delivers printed, embossed and encoded credit and debit cards on demand at branch level**. It seamlessly combines Matica's expertise in direct to card printing, embossing, and encoding in one compact desktop package.

The S3610 is **compliant with Visa® and Mastercard®** requirements. Its compact size in combination with its manual front feed/eject slot makes it ideal for self-service kiosk applications.

### Standard features



### Options



# ■ S3610 delivers...

- ► Highest quality 300dpi printing
- ▶ Up to 6 feeders and front manual feeder/eject
- ▶ Compact desktop design easily fits kiosks
- ► High-level security features
- ▶ Printing, embossing and tipping in one system
- ▶ Visa and Mastercard security compliance

### Ideal for

 Instant issuance of embossed, printed and encoded financial cards



- ► Contact and/or contactless chip encoding
- ► Six automatic feeders
- ► Smart Class Controller



# S3610

# Printer specifications

### Print technology

 Colour dve-sublimation and monochrome resin thermal transfer

### Print resolution

• 300dpi

### Print area

• 53.98 x 85.6mm / 3.370" x 2.125" (CR-80 cards)

### Print mode

· Single and dual-sided printing

### **Production speeds**

- · Magnetic stripe encoding, embossing, rear indenting, tipping - full cycle 58 seconds
- Plus one-side monochrome printing full cycle
- Plus one-side color printing full cycle 78 seconds

### **Embossing and Indenting**

- 72 characters drum rear indent
- Optional second drum 72 characters top indent

### Display

· LCD display 20x2

### Communications interface

• USB 2.0

### Printer dimensions (HxWxD)

- Single drum: 285x540x720mm (full config.)
- Double drum: 285x540x820mm (full config.)

### Printer weight

- · Single drum: 38kg (84lb)
- Dual drum: 45kg (100lb)

### Standard printer security

· Electronic and key control lock to secure card hoppers and reject-tray access

### Power supply

- 220-240V/110-115V, 50-60 Hz
- Standby mode and reduced power consumption

### Operating environment

- Temperature: 10°C 30°C, 50°F 86°F Humidity: 20% 80% (non-condensing)

### Storage conditions

- Temperature: -5°C to -70°C, 23°F to 158°F Humidity: 20% to 70% (non-condensing)

### Certifications

• RoHs, CE, CQC, WEEE

### Warranty

1 year or 50,000 cards (subject to the use of chromXpert® ribbons)

# Card specifications

### Card feeders

- · Front manual feeder/eject
- Front concealed card stacker: 30 cards
- 3 automatic feeders (optional up to x6): 100 cards each (0,76mm)
- · Rear concealed card stacker: 30 cards

### Reject bin

• 30 cards

### **Card format and materials**

• ISO CR80, ISO7810, ISO7816, ISO14443A&B

### Card thickness

• 0.64 mm - 0.89 mm (25 mils to 35 mils)

### Card types

• PVC, PVC Composite and PET

# Software specifications

### Operating system

• Windows 7, 10, 11 (32 & 64 bits)

- MaticardPro, REST API, MatiDeskDLL with interfacing SDK, Smart card
- SDK available for system integrators

# Options

### Extra card feeders

Up to 6 automatic feeders: 100 cards each (0.76mm)

### Magnetic stripe encoding

• Tracks 1, 2 & 3 ISO7811, HiCo/LoCo

### Smart card / Contactless encoding

• PC/SC EMV compliant contact and contactless chip encoding

### **Embossing and indenting**

 Optional dual drum of 72 characters with top indent for debit cards

### Communications interface

• LAN with single wire functionality (Smart Class controller) and real time cloud monitoring



# ▼ Consumables chrom pert

- · To ensure print quality and card durability, printhead lifespan and overall printer reliability, use chromXpert ribbons only.
- · Supply cores and cassettes are recyclable. Packaging is recycled.

Tipping ribbons	Part No.
• Tipping black (122 meters, approx 4000 cards)	B2.337.02.01
• Tipping White (122 meters, approx 4000 cards)	B2.337.02.15

Infiller ribbons	Part No
------------------	---------

- Infill black (122 meters, Approx yield REAR indent '7 chars' : 2,000 cards) **B2.337.00.03**
- Infill white (122 meters, Approx yield REAR indent '7 chars' : 2,000 cards) **B2.337.00.04**

ChromXpert™ ribbon program	Part No.
• YMCKO (250 prints)	PR22305301
Monochrome K (Black) (up to 2000 prints)	PR22314305
Monochrome White (up to 2000 prints)	PR22314308
Cleaning kit	PR20309601



## Global offices

Europe: Switzerland HQ, Italy

Asia: Malaysia, India

USA: South Carolina HQ, Minneapolis

Middle East: Dubai



Authorized reseller / System integrator

S3610 Datasheet A4 UK V5

Data subject to change without notice. All trademarks stated are the property of their respective owners

