S6200GE










Cost effective, mid-sized solution for embossing, printing and encoding cards





Designed to meet the specific needs of mid-volume card issuance programs, the S6200GE is a preconfigured printing, embossing, and tipping platform. It integrates proven proprietary technologies for high quality card production.

The S6200GE is versatile and has an excellent performance to price ratio, making it ideal for cost-conscious service bureaus, card manufacturers and financial institutions.

Delivering production volumes up to 600 cards per hour, the S6200GE is equipped with Matica's S1 dual-sided graphic printing unit and a 98 character embossing and indenting station. A magnetic encoder, and/or single contact/contactless or multi smart card encoders can be fitted as optional extras, to create an all-in-one solution for high performance, high speed card issuance.

A lamination module is also available to add a layer of visual security and increase the lifespan of the card.



■ S6200GE delivers...

- ▶ Thermal printing, embossing, indenting and tipping with optional card encoding
- ▶ Built upon proven, proprietary technology
- ▶ Modular, with flexible configuration and defined field upgradability
- ▶ PCI/DSS compliant software
- "Unlock" any field upgrade option

✓ Ideal for...

- ▶ Mid-volume issuance schemes at card personalization centers or within financial institutions
- ▶ Embossed EMV card personalization

Standard features















Warranty



Optional features





















S6200GE

Printer specifications

Print technology

- Monochrome thermal transfer and color dye-sublimation, direct-to-card
- · Embossing, indenting
- Tipping (black, silver, gold, white, blue and varnish)

Print resolution

• 300 dpi

Print area

· Near edge-to-edge

Speed

• Up to 600 cph

Embossing and indenting unit

· Single 98 characters

Printing

 Single S1 high speed graphic printing unit with flipover and dual-side cleaning station

Fonts

- · Standard Gothic and OCR7B emboss
- · OCRB1 and OCRB4 front indent
- OCRA1 and CVV2 rear indent
- Wide choice of country specific and other embossing/indent types

Communications interface

· USB 2.0, Ethernet

Printer dimensions (LxWxH)

• 1930 to 3050 x 550 x 1400 mm (76 to 120" x 22" x 55")

Power supply

· 220-240V/100-120V, 50-60 Hz

Operating environment

- Temperature: 15°C 30°C, 59°F 86°F
- · Humidity: 30% 70% (non-condensing)

Certifications

• RoHs, RoHS, CE, WEEE, Proposition 65

Warranty

- 1 year standard
- · +1 year extension available on request

Card specifications

Input /output hopper capacity

600 cards / 600 cards
 (Approx. 385 embossed cards)

Reject hopper capacity

· 30 cards

Card types

· ABS, PET, PVC

■ Software

Maticard Pro

- Windows® (32/64bit) 7, 8.1, 10, 11, Server 2012, 2016, 2019, 2022.
- · Diagnostic and setup software included
- · Smart card SDK optional

Encoding

Magnetic stripe

• Tracks 1, 2 & 3 ISO7811, HiCo/LoCo

Contact / Contactless

- EMV compliant contact chip encoding
- · EMV compliant contactless chip encoding

Options

Pro issuance kit

· Key locked cabinet, stack light, data encryption

Embossing and indenting unit

Additional 100 characters

Lamination

Smart secure laminator

Inline card mailing

· Card folding and envelope insertion

Xpress

• Smart card personalization and management software

Consumables

Printer ribbons

- Black monochrome ribbon: up to 11,200 prints per roll (45 mm length per card)
- 5-panel **YMCKO** color ribbon: 1,000 prints per roll
- 6-panel **YMCKOK** color ribbon: 800 prints per roll
- Half-panel YMCKO color ribbon (especially for photo):
 1,400 prints per roll
- *Other monochrome ribbons available on request

Tipping and Infill

- **Tipping ribbon**: Up to 4,000 prints per roll
- Color tipping: Black, silver, gold, white, blue and varnish
- Rear infill ribbon (7 ch/card): Up to 4,500 prints per roll
- Front infill ribbon (35 ch/card):
 Up to 1,800 prints per roll
- Color infill: black and white





Global offices

Europe: Switzerland HQ, Italy

Asia: Malaysia, India

USA: South Carolina HQ, Minneapolis

Middle East: Dubai



Authorized reseller / System integrator

Data subject to change without notice. All trademarks stated are the property of their respective owners.

S2600GE Datasheet A4 UK V1

