

# XID8600

## Print type



Retransfer  
dye sublimation

## 600 dpi



Resolution

## Distributed



Issuance

## Designed for ultra high-resolution secure card printing



Matica's **XID8600** is a **premium quality printer**, perfectly suited for the most demanding ID card programs requiring high definition and high security printing. Its 600dpi printhead delivers **outstanding image quality** combined with **security printing**, including microtext and covert UV printing to increase the number of Visual Security Elements (VSEs) on the card.

Built on the established XID series print engine, the XID8600 is durable and reliable. This, in combination with its high security print options, large capacity ribbons (1000 images) and its ability to print on durable card materials such as PC and ABS, make it ideal for **high-volume secure government ID schemes**, including driver's licenses and national ID cards.




## XID8600 delivers...

- ▶ 600 x 600dpi dual-sided printing
- ▶ 200 card input feeder / output hopper
- ▶ Robust and durable print engine
- ▶ Consistent print quality on multiple card surfaces/materials
- ▶ High capacity consumables (1000 images)
- ▶ Security printing including microtext and UV
- ▶ Up to 125 cards per hour
- ▶ USB and Ethernet







## Ideal for...

- ▶ Secure government ID card programs
- ▶ Increased card security
- ▶ Mid to high volume desktop issuance

### Standard features



### Optional features



# XID8600

## ■ Tailored, secure retransfer printing

The **XID8600 can be customized** according to a project's precise requirements. Both internal and external modules can be added to suit the required usage. Since sophisticated ID card applications normally require personalization on both sides of the card, the standard XID8600 model comes equipped for **duplex printing**, due to the factory-fitted built-in flipper module. A 200-card feeder and output hopper (for cards with a standard thickness of 0.76 mm) is similarly integrated.

For **secure technology based cards**, an inline contact or contactless chip encoder, as well as a magnetic stripe encoder are also available. The XID8600 can be seamlessly connected to single or dual-sided **inline lamination modules** (Matica's ILM-LS or ILM-DS) to increase the durability and tamper-resistance of cards.

## ■ Printer specifications

### Print technology

- Dye-sublimation, retransfer

### Print resolution

- 600 dpi

### Print area

- ISO CR-80, 85.60 x 53.98 mm

### Print speed

- Color: Up to 125 cards per hour (single-sided)

### Print mode

- Single and dual-sided

### Communications interface

- USB 2.0, Ethernet

### Printer security

- Support for Kensington® security lock

### Printer dimensions (HxWxD)

- 343 x 322 x 360 mm / 13.5" x 12.7" x 14.2"

### Weight

- 13.9 kg / 30.6 lb (excluding optional built-in items)

### Power supply

- 220-240V/100-120V, 50-60 Hz
- Standby mode and reduced power consumption

### Operating environment

- Temperature: 15°C to 30°C, 59°F to 86°F
- Humidity: 35% to 70% (non-condensing)

### Storage conditions

- Temperature: 5°C to 70°C, 23°F to 158°F
- Humidity: 20% to 70% (non-condensing)

### Certifications

- RoHs, CE, FCC, CQC, UL, WEEE, Proposition 65 (California, USA), Radio Equipment Directive (RED) (2014/53/EU)

### Warranty

- 3 years (subject to use of chromXpert® ribbons)
- Printhead: Lifetime warranty

## ■ Card specifications

### Input hopper capacity

- 200 cards (0.76 mm / 30 mil thickness)

### Output hopper capacity

- 100 cards, 100 reject bin

### Card thickness

- 0.25 mm - 1.02 mm / 10 mil - 40 mil (Hopper adjustment required)

### Card types

- ISO CR80, PVC, PVC-C, PET-F, PET-G, ABS, PC

## ■ Software specifications

### XPS printer driver

- Windows® (32/64bit) 7, 8.1, 10, 11, Server 2012, 2016, 2019, 2022.

## ■ Options

### Smart card / Contactless encoding

- Contact PC/SC, EMV compliant
- Smart contact station: ISO 7816-2
- ISO14443A, B, ISO15693, MIFARE®, DESFire®, HID iClass®

### Magnetic stripe

- ISO 7811 HiCo/LoCo (factory fit only)

### Lamination

- Inline single or dual-sided module



## ■ Consumables chromXpert

- To ensure print quality and card durability, printhead lifespan and overall printer reliability, use chromXpert ribbons only.
- Supply cores and cassettes are recyclable. Packaging is recycled.

ChromXpert™ ribbon program	Part No.
• YMCK (1000 prints)	Diamond: <b>PR000816</b>
• YMCKK (750 prints)	Diamond: <b>PR000817</b>
• YMCKUv (750 prints)	Diamond: <b>PR000813</b>
• K (2200 prints)	Diamond: <b>PR000815</b>
• YMCKPo (750 prints)	Diamond: <b>PR000818</b>
• RT film (750 prints)	Diamond: <b>PR000819</b>
• Cleaning Kit	<b>DIC10044</b>



## ■ Global offices

**Europe:** Switzerland HQ, Italy

**Asia:** Malaysia, India

**USA:** South Carolina HQ, Minneapolis

**Middle East:** Dubai



Authorized reseller / System integrator

Data subject to change without notice.  
All trademarks stated are the property of their respective owners.

XID8600 Datasheet A4 UK V5